

technical data

AXEL

PLASTICS RESEARCH LABORATORIES, INC.
MOLD RELEASES & INTERNAL LUBRICANTS

Mailing Address: Box 77 0855, Woodside, NY 11377
Shipping Address: 58-20 Broadway, Woodside, NY 11377
Tel: 718-672-8300 • Fax: 718-565-7447
E-mail: info@axelplastics.com

MOLD WIZ WB-640ET

General: A liquid external release agent that dries at room temperature forming a mono-molecular film which adheres by absorption to the mold walls and has no affinity for the resin. This selective adhesion prevents the film from easily being torn off by the demolded part resulting in numerous demoldings per release application without any necessity for washing the mold. Will not interfere with any secondary operations such as decorating, bonding, or painting.

Use: All types Epoxies, Phenolics, Polyester, Vinyl Ester, Natural & Synthetic Rubber

Composition: Proprietary resin emulsion of polyolefins, organic fatty acids and fatty glycerides in combination with wetting agents and surfactant in a water/alcohol vehicle.

TYPICAL PROPERTIES:

SOLIDS:	5.75 – 6.75%
COLOR:	Off White
SPECIFIC GRAVITY:	0.982 @ 25°C
VISCOSITY:	<50 cps @ 25°C
pH:	8.5 - 10.5
FLASH POINT:	Non Flammable
SHELF LIFE:	Minimum of one year

Application Instructions:

Clean mold with CLEAN WIZ. Spray a heavy coat to break-in the mold. Let it dry. Spray a thin coat (fine mist to dry film) and allow to dry completely with no moisture residue. Accelerate drying time by blowing hot air or by using heat lamps if necessary. Repeat whenever mold has been cleaned or as required to give mold release properties.

All information given by us about our products is based upon our tests and experience. It is intended for use by persons having technical skill at their own discretion and risk, and we assume no liability in connection with their use.

(062209)